

**Solution Manual for Fundamentals of Structural Analysis 5th
Edition by Leet Uang Lanning**

ISBN 0073398004 9780073398006

Full link download:

Solution Manual:

<https://testbankpack.com/p/solution-manual-for-fundamentals-of-structural-analysis-5th-edition-by-leet-uang-lanning-isbn-0073398004-9780073398006/>

FUNDAMENTALS OF STRUCTURAL ANALYSIS


5th Edition

Kenneth M. Leet, Chia-Ming Uang, Joel T. Lanning, and Anne M. Gilbert

SOLUTIONS MANUAL


CHAPTER 2: DESIGN LOADS AND STRUCTURAL FRAMING

P2.1. Determine the deadweight of a 1-ft-long segment of the prestressed, reinforced concrete tee-beam whose cross section is shown in Figure P2.1. Beam is constructed with lightweight concrete which weighs 120 lbs/ft.



P2.1

Compute the weight/ft. of cross section @ 120 lb/ft.



Compute cross sectional area:



$$\text{Area} = (0.5 \times 6') + 2 \left[\frac{1}{2} \times 0.5' \times 2.67' \right] + (0.67' \times 2.5') + (1.5' \times 1')$$

$$= 7.5$$

Weight of member per foot length:

$$\text{wt/ft} = 7.5 \text{ ft}^2 \times 120 \text{ lb/ft} = 900 \text{ lb/ft}$$

P2.2. Determine the deadweight of a 1-ft-long segment of a typical 20-in-wide unit of a roof supported on a nominal 2 x 16 in. southern pine beam (the actual dimensions are } in. smaller). The 3/4-in. plywood weighs 3 lb/ft.



See Table 2.1 for weights
wt/20" unit

$$\text{Plywood: } 3 \text{ psf} \times \frac{20''}{12} \times 1' = 5 \text{ lb}$$

$$\text{Insulation: } 3 \text{ psf} \times \frac{20''}{12} \times 1' = 5 \text{ lb}$$

$$\text{Roof g Tar \& G: } 5.5 \text{ psf} \times \frac{20''}{12} \times 1' = \frac{9.171 \text{ lb}}{19.171 \text{ b}}$$


$$\text{Wood Joist} = 37 \frac{\text{lb}}{\text{ft}} \times \frac{1.5''}{12} \times 1' = 5.97 \frac{\text{lb}}{\text{ft}}$$

$$\text{Total wt of 20" unit} = 19.17 + 5.97 = 25.14 \text{ lb. Ans.}$$

P2.3. A wide flange steel beam shown in Figure P2.3 supports a permanent concrete masonry wall, floor slab, architectural finishes, mechanical and electrical systems. Determine the uniform dead load in kips per linear foot acting on the beam.

The wall is 9.5-ft high, non-load bearing and laterally braced at the top to upper floor framing (not shown). The wall consists of 8-in. lightweight reinforced concrete masonry units with an average weight of 90 psf. The composite concrete floor slab construction spans over simply supported steel beams, with a tributary width of 10 ft, and weighs 50 psf.

The estimated uniform dead load for structural steel framing, fireproofing, architectural features, floor finish, and ceiling tiles equals 24 psf, and for mechanical ducting, piping, and electrical systems equals 6 psf.



P2.3

Uniform Dead Load W_A acting on the Wide Flange Beam:

Wall Load:

$$9.5'(0.09 \text{ ksf}) = 0.855 \text{ kif}$$

Floor Slab:

$$10'(0.05 \text{ ksf}) = 0.50 \text{ kif}$$

Steel Frmg, Fireproof'g, Arch'l Features, Floor Finishes, & Ceiling:

$$10'(0.024 \text{ ksf}) = 0.24 \text{ kif}$$


Mech'I, Piping & Electrical Systems:

$$10'(0.006 \text{ ksf}) = 0.06 \text{ kif}$$

$$\hline \text{Total } W_A = 1.66 \text{ kif}$$

P2.4. Consider the floor plan shown in Figure P2.4. Compute the tributary areas for (a) floor beam B1, (b) floor beam B2, (c) girder G1,

(d) girder G2, (e) corner column C1, and (f) interior column C



«Caw • - [;)to) - [z -soi]

6 7

(b) Method 1: $AT = (20 + 20) \times 20 = 1AT = 66.7 \text{ ft}^2$

Method 2: $AT = 320 - 4(3.33 \times 4) = 1AT = 288 \text{ ft}^2$

Method 2: $AT = 66.7 - 2(3.33 \times 3.33) = 1AT = 55.6 \text{ ft}^2$

(c) Method 1: $AT = (20 + 10)(10)$

[s, -166.7n]
 «a - - ['ao»)e2 [, s»]
 [s -so.6n]


(d) Method 1: $A_2 = \frac{40 + 20}{2} (36)$

[s, -1080n]

Method 2: $AT = 1080 + 2(3.33 \times 4)$

[s -1006n]


5 Zs»]




a-

5 @ 8' = 40

GM - 40' (20) (4' 20) I - 900n, |
 ()
 Copyright © 2018 McGraw-Hill Education. All rights reserved.
 No reproduction or distribution without the prior written consent of McGraw-Hill Education.




1: $A_T = 66$
 $\left(\frac{20}{2}\right)$
 $2 \quad 2 \quad 2$ A_T



P2.5. Refer to Figure P2.4 for the floor plan.
Calculate the tributary areas for (a) floor beam



B3, (b) floor beam B4, (c) girder G3, (d) girder G4, (e) edge column C3, and (f) corner column C4.




(a) Method 1: $A_t = (10)(20)$

$$[s, -200]$$

Method 2: $A_t = 200 - 4(5) = 180$


$$[s - 180]$$



(b) Method 1: $A_t = (6.67)(20) = 133.4$

Method 2: $A_t = 133.4 - 4(3.33) = 118.6$

$$[s - 118.6]$$



(c) Method 1: $A_t = (36)(20) = 720$



Method 2: $A_t = 720 + 2(36) = 804$

(d) Method 1: $A_t = (4)(40) + 33.33(10) = 433.33$

$$[s, -466.67]$$

$$[s - 466.67]$$

$$[s, -466.67]$$



(e) $A_t = (30)(20) = 600$

B4

2 @ 10' = 20'

e

G3






G2

5 @ 8' = 40'

2-6








Copyright © 2018 McGraw-Hill Education. All rights reserved.

No reproduction or distribution without the prior written consent of McGraw-Hill Education.



d2:

2




2-6

Copyright © 2018 McGraw-Hill Education. All rights reserved.

No reproduction or distribution without the prior written consent of McGraw-Hill Education.

P2.6. The uniformly distributed live load on the floor plan in Figure P2.4 is 60 lb/ft. Establish the loading for members (a) floor beam B1,

(b) floor beam B2, (c) girder G1, and (d) girder G2. Consider the live load reduction if permitted by the ASCE standard.



P2.4

$$L = 60 \left(0.25 + \frac{15}{2} \right) = 50.6 \text{ psf} > \frac{0}{2} \text{ ok}$$

(a) $A = 8(40) = 320 \text{ ft}^2$, $K_L = 2$, $A_r K_L = 640 > 400$

$$w = 8(50.6) = 404.8 \text{ lb/ft} = 0.40 \text{ kips/ft}$$

w
B1 and B2

(b) $A = \frac{6.67}{2}(20) = 66.7 \text{ ft}^2$, $K_L = 2.4$, $A_r K_L = 133.4 < 400$, No Reduction

$$w = \frac{6.67}{2}(60) = 200.1 \text{ lb/ft} = 0.20 \text{ kips/ft}$$

(c) $A = \frac{6.67}{2}(20) + 10(10) = 166.7 \text{ ft}^2$, $K_L = 2$, $A_r K_L = 333.4 < 400$, No Reduction

$$w = \frac{6.67}{2}(60) = 200.1 \text{ lb/ft} = 0.20 \text{ kips/ft}$$





$$P = \frac{40W}{2} = \frac{60(10)(20)}{2} = 6000 \text{ lbs} = 6 \text{ kips}$$

(d) $A = \left(\frac{40}{2} + \frac{20}{2} \right) 36 = 1080 \text{ ft}^2$, $K_{LL} = 2$, $A_r K_{LL} = 2160 > 400$

$$L = 60 \left(0.25 + \frac{35}{\sqrt{2160}} \right) = 34.4 > \frac{60}{2} \text{ ok}$$

$$L = 34.4 \text{ psf}$$


$$P = 8(34.4) \left(\frac{40}{2} + \frac{20}{2} \right) = 8256 \text{ lbs} = 8.26 \text{ kips}$$



Copyright © 2018 McGraw-Hill Education. All rights reserved.

No reproduction or distribution without the prior written consent of McGraw-Hill Education.

P2.7. The uniformly distributed live load on the floor plan in Figure P2.4 is 60 lb/ft. Establish the loading for members (a) floor beam B3, (b) floor beam B4, (c) girder G3, and girder G4. Consider the live load reduction if permitted by the ASCE standard.



P2.4

(a) $A = 10(20) = 200 \text{ ft}^2$, $K_L = 2$, $A, K_L = 400 > 400$

$$w = 10(60) = 600 \text{ lb/ft} = 0.60 \text{ kips/ft}$$



B3 and B4


(b) $A = 6.67(20) = 133.4 \text{ ft}^2$, $K_L = 2$, $A, K_L = 266.8 < 400$, No Reduction

$$w = 6.67(60) = 400.2 \text{ lb/ft} = 0.40 \text{ kips/ft}$$

(c) $A = 36(20) = 720 \text{ ft}^2$, $K_L = 2$, $A, K_L = 1440 > 400$

$$L = 60 \left[0.25 + \frac{60}{\sqrt{1440}} \right] = 38.7 \text{ psf}$$

$$P = \frac{38.7(840)}{2} = 6192 \text{ lbs} = 6.19 \text{ kips}$$




G3

(d) $A = \left(\frac{3}{4}\right) 40 + 33.33(10) = 493.3 \text{ ft}^2$, $K_{LL} = 2.4$, $A, K_{LL} = 986.6 > 400$

$$L = 60 \left[0.25 + \frac{60}{\sqrt{986.6}} \right] = 43.7 > \frac{60}{2}, \text{ ok}$$

$$P = \frac{43.7(6.67(20))}{2} = 2914.8 \text{ lbs} = 2.91 \text{ kips}$$




G4

*Copyright© 2018 McGraw-Hill Education. All rights reserved.
No reproduction or distribution without the prior written consent of McGraw-Hill Education.*

P2.8. The building section associated with the floor plan in Figure P2.4 is shown in Figure P2.8. Assume a live load of 60 lb/ft² on all three floors. Calculate the axial forces produced by the live load in column C1 in the third and first stories. Consider any live load reduction if

permitted by the ASCE standard.



P2.8

$$(a) A = (40 + 20)(40 + 20) = 900 \text{ ft}^2, K = 4, A K = 3600 > 400$$


$$L = 60 \left[0.25 + \frac{1.5}{\sqrt{3600}} \right] = 30 \text{ psf} \quad \text{ok (minimum permitted)}$$



$$P_{1,1} = \frac{900}{3600}$$

$$P_{1,1} = 900(30) = 27000 \text{ lbs} = 27 \text{ kips}$$

$$P_{1,2} = 900(30) = 27000 \text{ lbs} = 27 \text{ kips}$$



tP
r
C2


ELEVATION

*Copyright © 2018 McGraw-Hill Education. All rights reserved.
No reproduction or distribution without the prior written consent of McGraw-Hill Education.*

P2.9. The building section associated with the floor plan in Figure P2.4 is shown in Figure

P2.8. Assume a live load of 60 lb/ft² on all three floors. Calculate the axial forces produced by the live load in column C3 in the third and first stories. Consider any live load reduction if

permitted by the ASCE standard.





P2.8

$$L_A = \frac{4(20)}{2} = 40 \text{ ft}, K = 4, AK = 160 > 400$$

$$L = 60 \left(0.25 + \frac{15}{\sqrt{2400}} \right) = 33.4 \text{ psf} \approx \frac{60}{2} \text{ ok}$$

$$P_{1st} = (600)(33.4) = 20040 \text{ lbs} = 20.0 \text{ kips}$$


$$P_{3rd} = (600)(33.4) = 60120 \text{ lbs} = 60.1 \text{ kips}$$



ELEVATION


P2.10. A five-story building is shown in Figure P2.10. Following the ASCE standard, the wind pressure along the height on the windward side has been established as shown in Figure

P2.10(c). (a) Considering the windward pressure in the east-west direction, use the tributary area concept to compute the resultant wind force at each floor level. (b) Compute the horizontal base shear and the overturning moment of the building.



a) Resultant Wind Forces

- Roof 20 psf (6 x 90) = 10,800 lb
- 5th floor 20 psf (12 x 90) = 21,600 lb
- 4th floor 20 psf (2 x 90) + 15 (10 x 90) = 17,100 lb
- 3rd floor 15 psf (10 x 90) + 13 (2 x 96) = 15,800 lb
- 2nd floor 13 psf (12 x 90) = 14,040 lb



b) Horizontal Base Shear $V_{\sim} = 2$ Forces at Each Level =


$$10.8' + 21.6' + 17.1' + 15.8' + 14.04' = \dots = [9.3@] \quad (a)$$

Overturning Moment of the Building =

$$2(\text{Force @ Ea. Level} \times \text{Height above Base})$$

$$10.8' (60') + 21.6 (48) + 17.1 (36) + 15.8(24) + 14.04'(12)' =$$


$$M \text{ overturning} = [2, 848''$$



P2.11. A mechanical support framing system is shown in Figure P2.11. The framing consists of

steel floor grating over steel beams and entirely supported by four tension hangers that are connected to floor framing above it. It supports

light machinery with an operating weight of 4000 lbs, centrally located. (a) Determine the impact factor I from the *Live Load Impact Factor*, Table 2.3. (b) Calculate the total live load acting on one hanger due to the machinery and uniform live load of 40 psf around the machine. (c) Calculate the total dead load acting on one hanger. The floor framing dead load is 25 psf. Ignore the weight of the hangers. Lateral bracing is located on all four edges of the mechanical floor framing for stability and transfer of lateral loads.



Section (b)

P2.11

$$= 4.8^k$$

a) Live Load Impact Factor = 20% \times _____

b) Total LL

Machinery = 1.20 (4 kips)

Uniform LL = ((10' 16') - (5' 10'))(0.04ksf) = 4.4

Total LL = $\frac{9.2'}{4}$

\therefore Total LL Acting on One Hanger = $\frac{9.2'}{4}$ Hangers = [2.3]

c) Total DL


Floor Framing = 10' x 16' (0.025 ksf)

\therefore Total DL Acting on one Hanger = $\frac{4'}{4}$ Hangers = [1 kip]

\therefore Total DL + LL on One Hanger = 2.3' + 1' = 3.3 kips

*Copyright © 2018 McGraw-Hill Education. All rights reserved.
No reproduction or distribution without the prior written consent of McGraw-Hill Education.*

P2.12. The dimensions of a 9-m-high warehouse are shown in Figure P2.12. The windward and leeward wind pressure profiles in the long direction of the warehouse are also shown. Establish the wind forces based on the following information: basic wind speed = 40 mis, wind exposure category = C, $K_z = 0.85$, $K_d = 1.0$, $G = 0.85$, and $C_s = 0.8$ for windward wall and -0.2 for leeward wall. Use the K_z values listed in Table 2.4. What is the total wind force acting in the long direction of the warehouse?



P2.12

Use $I = 1$

$$q_z = 0.613 V \quad (\text{Eq. 2.4b})$$

$$= 0.613 @ 40 = [980.8 \text{ N/m}]$$

$$= 980.8 \text{ N/m}$$

$$q_z = 980.8 (K_z K_d) = [833.7 K_z]$$

$$0-4.6\text{m}: q_z = 833.7(0.85) = 708.6 \text{ N/m}$$

$$4.6-6.1\text{m}: q_z = 833.7(0.90) = 750.3 \text{ N/m}$$

$$6.1-7.6\text{m}: q_z = 833.7(0.94) = 783.7 \text{ N/m}$$

$$7.6-9\text{m}: q_z = 833.7(0.98) = 817.1 \text{ N/m}$$

For the Windward Wall

$$p = GC_s \quad (\text{Eq. 2.7})$$

$$\text{where } GC_s = 0.85(0.8) = [0.68]$$

$$p = 0.68 q_z$$

$$0-4.6\text{m} \quad p = 481.8 \text{ N/m}$$

$$4.6-6.1\text{m} \quad p = 510.2 \text{ N/m}$$

$$6.1-7.6\text{m} \quad p = 532.9 \text{ N/m}$$

$$7.6-9\text{m} \quad p = 555.6 \text{ N/m}$$

Total Windforce, F_w , Windward Wall

$$F_w = 481.8[4.6 \times 20] + 510.2[1.5 \times 20]$$

$$+ 532.9[1.5 \times 20] + 555.6[1.4 \times 20]$$

$$F_w = 91,180 \text{ N}$$

For Leeward Wall

$$p = GC_s = q_z (0.85)(-0.2)$$

$$s = q_z \text{ at } 9\text{m} = 817.1 \text{ N/m (above)}$$

$$p = 817.1 (0.85)(-0.2) = -138.9 \text{ N/m}$$

Total Windforce, F_l , on Leeward Wall

$$F_l = (20 \times 9)(-138.9) = [-25,003 \text{ N}]$$


Total Force = $F_w + F_l$

$$= 91,180 \text{ N} + 25,003$$

$$= [116,183.3 \text{ N}]$$

Both F_w and F_l Act in Same Direction.

P2.13. The dimensions of an enclosed gabled building are shown in Figure P2.13a. The external pressures for the wind load perpendicular to the ridge of the building are shown in Figure P2.13b. Note that the wind pressure can act toward or away from the windward roof surface. For the particular building dimensions given, the C_p value for the roof based on the ASCE standard can be determined from Table P2.13, where plus and minus signs signify pressures acting toward and away from the surfaces, respectively. Where two values of C_p are listed, this indicates that the windward roof slope is subjected to either positive or negative pressure, and the roof structure should be designed for both loading conditions. The ASCE standard permits linear interpolation for the value of the inclined angle of roof θ . But interpolation should only be carried out between values of the same sign. Establish the wind pressures on the building when positive pressure acts on the windward roof. Use the following data: basic wind speed = 100 mi/h, wind exposure category = B, $K_s = 0.85$, $K_z = 1.0$, $G = 0.85$, and $C_e = 0.8$ for windward wall and -0.2 for leeward wall.




P2.13

TABLE P2.13 Roof Pressure Coefficient C_p

* θ defined in Figure P2.13

	Windward								Leeward		
Angle θ	10	15	20	25	30	35	45	>60	10	15	>20
C_p	-0.9	-0.7	-0.4	-0.3	-0.2	-0.2	0.0	0.01	-0.5	-0.5	-0.6
			0.0	0.2	0.2	0.3	0.4				



Mean Roof Height, $h = 24$ ft

$$\theta = \tan^{-1} \left(\frac{24}{48} \right) = 33.69^\circ \quad (\text{for Table 2.10})$$

Consider Positive Windward Pressure on Roof, i.e. left side.
Interpolate in Table P2.10

$$C_p = 0.2 + \frac{(33.69 - 30)}{(35 - 30)} (0.1)$$

$$C_p = 0.2738 \text{ (Roof only)}$$

From Table 2.4 (see p48 of text)

$$K_s = 0.57, 0 - 15'$$

$$= 0.62, 15' - 20'$$

$$= 0.66, 20' - 25'$$

$$= 0.70, 25' - 30'$$

$$= 0.76, 30' - 32'$$

P2.13. Continued

$$K_s = 1.0, K_z = 0.85, I = 1$$

$$q_s = 0.00256 V^2 \text{ (Eq 2.4a)}$$

$$q_s = 0.00256(100)^2 = 25.6 \text{ psf}$$

$$K_d = 0.85, K_e = 0.85, K_z = 0.85$$

$$0-15'; q_s = 25.6(1)(0.85)(1)(0.85) = 12.40 \text{ lb/ft}$$

$$15-16'; q_s = 13.49 \text{ lb/ft}$$

$$h = 24'; q_s = 14.36 \text{ b/ft}$$

Wind Pressure on Windward Wall & Roof

$$P = q_s C_d C_e$$

$$\text{Wall } 0-15' P = 12.40 \times 0.85 \times 0.80$$

$$P = [8.43 \text{ psf}]$$

$$\text{Wall, } 15'-16' P = 13.49 \times 0.85 \times 0.8 = [9.17 \text{ psf}]$$

$$\text{Roof, } P = 14.36 \times 0.85 \times 0.2738$$

$$P = [3.34 \text{ psf}]$$

Wind Pressure on Leeward Side

$$\text{For Wall } P = q_s C_d C_e$$

$$\text{For } h = 24'; q_s = q_s = 14.36 \text{ b/ft}$$

$$C_d = 0.2 \text{ for wall} = 0.6 \text{ for roof}$$

$$\text{For Wall } P = 14.36 (0.85)(0.2)$$

$$P = 2.44 \text{ lb/ft}$$

$$\text{For Roof } P = 14.36 (0.85)(-0.6)$$

$$P = [-7.32 \text{ lb/ft}]$$

P2.14. Establish the wind pressures on the building in Problem P2.13 when the windward roof is subjected to an uplift wind force.




TABLE P2.13 Roof Pressure Coefficient C_r

* θ defined in Figure P2.11

	Windward								Leeward		
Angle θ	10	15	20	25	30	35	45	>60	10	15	>20
C_r	-0.9	-0.7	-0.4	-0.3	-0.2	-0.2	0.0	0.01	-0.5	-0.5	-0.6
			0.0	0.2	0.2	0.3	0.4				

See P2.13 Solution

Windward Roof (Negative Pressure)

$$\theta = 33.7^\circ$$

Interpolate between 30° and 35° for negative C_r value in Table P2.12


$$C_r = -0.274$$

$$p = q_z G C_r = 21.76(0.66)(-0.274)$$

$$= [-3.34 \text{ lb/ft}^2] \text{ (suction)}$$

Note: Wind pressures on other 3 surfaces are the same as in P2.13.

P2.15. (a) Determine the wind pressure distribution on the four sides of the 10-story hospital shown in Figure P2.15. The building is located near the Georgia coast where the wind velocity contour map in the ASCE Standard specifies a design wind speed of 140 mph. The building, located on level flat ground, is classified as *stiff* because its natural period is less than 1 s. On the windward side, evaluate the magnitude of the wind pressure every 35 ft in the vertical direction. (b) Assuming the wind pressure on the windward side varies linearly between the 35-ft intervals, determine the total wind force on the building in the direction of the wind. Include the negative pressure on the leeward side.



(a) Compute Variation of Wind Pressure on Windward Face

$$V = 140 \text{ mph, Eq 2.8}$$

$$q_s = 0.00256 V^2 \text{ Eq 2.6a}$$

$$= 0.00256 (140)^2$$

$$q_s = 50.176 \text{ psf; Round to } 50.18 \text{ psf}$$

$$I = 1.15 \text{ for hospitals}$$

$$K_z = 1.03 \text{ at } 0 \text{ ft}$$

K_z , Read in Table 2.4

Elev. (ft)	0	35'	70'	105'	140'
K_z	1.03	1.19	1.34	1.44	1.52

$$q_s = 50.18 (1.15)(0.85)$$

$$q_s = 49.05 \text{ psf}$$

Compute Wind Pressure "p" on Windward Face

$$p = q_s C_p = 49.05 K_z C_p$$

where $G = 0.85$ for natural period less than 1 sec.

$$C_p = 0.8 \text{ on windward side}$$

$$p = 49.05 K_z (0.85)(0.8) = [33.354 K_z]$$

Compute "p" for Various Elevations

Elev. (ft)	0	35	70	105	140
P (psf)	34.36	39.69	44.69	48.03	50.70

Compute Wind Pressure on Leeward Wall

$$p = q_s C_p C; \text{ Use Value of } q_s \text{ at } 140 \text{ ft. i.e. } K_z = 1.52$$

$$C_p = -0.5 \quad q_s = 49.05 (1.52) = [74.556]$$

$$p = 74.556 C; = 74.556 (0.85) (-0.5)$$


$$p = -31.68 \text{ psf] ANS. Wind}$$

Pressure on Side Walls $p = q_s C_p$

$$= 49.05 (1.52) (0.85) (-0.7)$$

$$p = -44.36 \text{ psf]$$

(b) Variation of Wind Pressure on Windward and Leeward Sides



P2.15. Continued

Compute Total Wind Force (kips)

$$F_1 = \frac{50.7 + 48.02[35 \times 160]}{2 \times 1000} = 276.42 \text{ kip}$$

$$F_2 = \frac{48.03 + 44.69[35 \times 160]}{2 \times 1000} = 259.62 \text{ k}$$

$$F_3 = \frac{44.69 + 39.69[35 \times 160]}{2 \times 1000} = 236.26 \text{ k}$$


$$F_4 = \frac{39.69 + 34.36[35 \times 160]}{2 \times 1000} = 207.39 \text{ k}$$

$$F_5 = \frac{31.68(140 + 160)}{2 \times 1000} = 709.63 \text{ k}$$

$$\begin{aligned} \text{Total Wind Force} &= 2F_1 + F_2 + F_3 + F_4 + F_5 \\ &= [1689.27 \text{ k}] \end{aligned}$$

P2.16. Consider the five-story building shown in Figure P2.10. The average weights of the floor and roof are 90 lb/ft and 70 lb/ft, respectively. The values of S_s and S_1 are equal to $0.9g$ and $0.4g$, respectively. Since steel moment frames are used in the north-south direction to resist the seismic forces, the value

of R equals 8. Compute the seismic base shear V . Then distribute the base shear along the height of the building.



Fundamental Period

$$T = C T_{4/4} \quad [C_s = 0.035 \text{ for steel moment frames}]$$

$$T = 0.035(60)^{0.4}$$

$$T = [0.75 \text{ sec}]$$

$$W = 4(100 \times 90) 90 \text{ lb/ft}^2 + (100 \times 90) 70 \text{ lb/ft}$$

$$= 3,870,000 \text{ lbs} = [3,870 \text{ kips}]$$

$$V = \frac{S_s W}{T(R/I)} \quad I = 1 \text{ for office bldgs.}$$

$$V = \frac{0.4(3870)}{0.75(8/1)} = [258 \text{ kips}]$$

$$R = \frac{S_s W}{V} = \frac{0.9(3870)}{258} = [4.5]$$

$$C_s = 0.04411 S_s W$$

$$C_s = 0.0441 (1)(0.9)(3870)$$

$$= [153.6 \text{ kips}]$$

Therefore, Use $V = 258 \text{ kips}$

$$F_x = \frac{W_x}{\sum_{i=1}^n W_i} V$$

$$F_x = \frac{W_x}{\sum_{i=1}^n W_i} V$$

P2.16. Continued

Forces at Each Floor Level

Floor	Weight W_x , (kips)	Floor Height h_x , (ft)	$W_x J_x$	$\frac{W_x J_x}{2W_x h_x^k}$	F_x , (kips)
Roof	630	60	63,061	0.295	76.1
5 th	810	48	63,079	0.295	76.1
4 th	810	36	45,638	0.213	56.0
3 rd	810	24	28,922	0.135	34.8
2 nd	810	12	13,261	0.062	16.0
	$\Sigma=3,870$		$\Sigma=213,961$		$\Sigma=258$

P2.17. When a moment frame does not exceed 12 stories in height and the story height is at least 10 ft, the ASCE standard provides a simpler expression to compute the approximate fundamental period:

$$T = 0.1N$$

where N = number of stories. Recompute T with the above expression and compare it with that obtained from Problem P2.16. Which method produces a larger seismic base shear?

ASCE Approximate Fundamental Period:


$$T = 0.1N$$

$$N=5 \quad \therefore T = 0.5 \text{ seconds}$$

$$V = \frac{0.3 \times 6750}{0.5(5/1)} = 810 \text{ kips}$$

The simpler approximate method produces a larger value of base shear.

P2.18. (a) A two-story hospital facility shown in Figure P2.18 is being designed in New York with a basic wind speed of 90 mi/h and wind exposure *D*. The importance factor *I* is 1.15 and $K_z = 1.0$. Use the simplified procedure to determine the design wind load, base shear, and building overturning moment. (b) Use the equivalent lateral force procedure to determine the seismic base shear and overturning moment. The facility, with an average weight of 90 lb/ft for both the floor and roof, is to be designed for the following seismic factors: $S_{vs} = 0.27g$ and $S_{vs} = 0.06g$; reinforced concrete frames with an *R* value of 8 are to be used. The importance factor *I* is 1.5. (c) Do wind forces or seismic forces govern the strength design of the building?



(a) Wind Loads Using Simplified Procedure:

Design Wind Pressure $P_s = K_z I P_g$

$2. = 1.66$ Table 2.8, Mean Roof Height = 30'

Zones P_s $P_s = 1.66(1)1.15P_g = 1.909P_g$

A	12.8 psf	24.44 psf
C	8.5 psf	16.22 psf

Resultant Force at Each Level; Where Distance $a = 0.1(100') = 10'$; $0.4(30') = 12'$; $3'$

$a = 10'$ Controls & $2a = 20'$ Region (A)

$$F_{z, \text{moor}} \text{ Zone (A): } \frac{15'}{2} (24.44 \text{ psf}) \frac{20'}{1000} = 3.67'$$

$$\text{Zone (C): } \frac{15'}{2} (16.3 \text{ psf}) \frac{80'}{1000} = 9.78'$$

$$\underline{\underline{F_{z, \text{Resultant}} = 13.45'}}$$

$$F_{z, \text{4}} \text{ Zone (A): } 15' (24.44 \text{ psf}) \frac{20'}{1000} = 7.33'$$


$$\text{Zone (C): } 15' (16.3 \text{ psf}) \frac{80'}{1000} = 19.56'$$

$$\underline{\underline{F_{z, \text{se}} = 26.89'}}$$

Base Shear $V = F_{z, \text{moor}} + F_{z, \text{4}} = [40.34]$

Overturning Moment $M_{o, \text{moor}} = 2Fh$

$$M_{o, \text{moor}} = 13.45(100') + 26.89(15') = [2000 \text{ @}]$$



P2.18. Continued

(b) Seismic Loads by Equivalent Lateral Force Procedure Given: $W = 90$ psf Floor & Roof;

$S_s = 0.27g, S_{vs} = 0.06g; R = 8, I = 1.5$

Base Shear $V_{base} = \frac{S_s W}{R I}$

Where W Total Building Dead Load =

$W_f = 90 \text{ psf} (100' \cdot 2) = 900'$

$W_{ro} = 90 \text{ psf} (100' \cdot 2) = 900'$

$W_t = 1800'$

And $T = C_s h_s = 0.342 \text{ sec.}$

$C_s = 0.016$ Reinf. Concrete Frame

$X = 0.9$ Reinf. Concrete Frame

$h = 30'$ Building Height

$V_{base} = \frac{0.06(1800')}{(0.342 \text{ sec})(8/1.5)} = 0.33W = \frac{59.2'}{\text{Controls}}$

$V_{max} = \frac{S_s W}{R I} = \frac{0.27(1800')}{(8/1.5)} = 0.051W = 91.1'$

$V_e = 0.044 S_s I W = 0.044(0.27)(1.5)(1800')$
 $= 0.0178W = 32.1'$

Force @ Each Level $F_i = \frac{W_i h_i}{\sum W_i h_i} V_e$, Where $V_e = 59.2'$

$T < 0.5 \text{ Sec. Thus } K = 1.0$

Level	W_i	H_i	$W_i h_i$	$W_i h_i / \sum W_i h_i$	Force @ Ea. Level:
Roof	900'	30'	27000	0.667	$F_{ro} = 39.5'$
2 ^o	900'	15'	13500	0.333	$F_{2o} = 19.76'$
					$F_x = V_{base} = 59.2'$


Overtuning Moment $M_{ov} = F_i h_i$ $\sum W_i h_i^k = 40500$

$M_{ov} = 39.5'(30') + 19.76'(15') = [1,481.4 \text{ ft}]$


(c) Seismic Forces Govern the Lateral Strength Design.

P2.19. In the gabled roof structure shown in Figure P2.13, determine the sloped roof snow load P . The building is heated and is located in a windy area in Boston. Its roof consists of asphalt shingles. The building is used for a manufacturing facility, placing it in a type II occupancy category. Determine the roof slope

factor, C , using the ASCE graph shown in Figure P2.19. If roof trusses are spaced at 16 ft on center, what is the uniform snow load along a truss?



P2.19



P2.13

Sloped Roof Snow Load $P = C_s p_f$

Where p_f Flat Roof Snow Load

$$p_f = 0.7 C_e C_t I p_g$$

$C_e = 0.7$ Windy Area

$C_t = 1.0$ Heated Building

$I = 1.0$ Type II Occupancy

$p_g = 40$ psf for Boston

$C_s = 0.9$ (Non-Slippery Surface)

$$C_s = \text{Based on Roof Slope } \theta = \tan^{-1} \left(\frac{16}{24} \right) = 33.7^\circ$$

From Fig. P2.17 C is Approximately 0.9 (Non-Slippery Surface)

$$P_s = 0.7 (0.7)(1.0)(1.0)(40 \text{ psf}) = 19.6 \text{ psf}$$

$$P = C P_s = 0.9 (19.6 \text{ psf}) = [17.64 \text{ psf}]$$

Uniform Load Acting on Trusses Spaced @ 16' O.C.

$$W_s = [17.64 \text{ psf} (0.6')] = [282.2 \text{ plf}]$$

P2.20. A beam that is part of a rigid frame has end moments and mid-span moments for dead, live, and earth-quake loads shown below. Determine the governing load combination for both negative and positive moments at the ends and mid-span of the beam. Earthquake load can act in either direction, generating both negative and positive moments in the beam.

End Moments (ft-kip)	Mid-Span Moments (ft-kip)
Dead Load -180	+90
Live Load -150	+150
Earthquake ±80	0

Load Combinations-Factored Strength

End Moments

$$1.4DL = 1.4(-180\text{ft}\cdot\text{k}) = -252\text{ft}\cdot\text{k}$$

$$1.2DL + 1.6LL + 0.5E = 1.2(-180) + 1.6(-150) + (-80) = -456\text{ft}\cdot\text{k}$$

$$1.2DL \pm LOE + LL + 0.2E = 1.2(-180) + (-80) + (-150) = -446\text{ft}\cdot\text{k}$$

Mid-Span Moments

$$1.4DL = 1.4(+90\text{ft}\cdot\text{k}) = +126\text{ft}\cdot\text{k}$$


$$1.2DL + 1.6LL + 0.5E = 1.2(+90) + 1.6(+150) + 0 = +348\text{ft}\cdot\text{k}$$

$$1.2DL \pm LOE + LL + 0.2E = 1.2(90) + 0 + (150) = +258\text{ft}\cdot\text{k}$$

Beam Needs to be Designed for Max. End Moment = -456 ft·k

Max. Mid-Span Moment = +348 ft·k

P2.21. Calculate the vertical hydrostatic load on the 5100-lb empty shipping container in Figure P2.19 subjected to a tsunami inundation height of 3'. Assuming the container is water-tight, will the tsunami wave be capable of carrying away the container as debris?



$$F_v = \gamma_w h A = (62.4 \text{ lb/ft}^3)(3 \text{ ft})(8 \text{ ft})(20 \text{ ft})$$

$$F_v = 33792 \text{ lbs}$$


$$F_v = 33.8 \text{ kips}$$

$$33.8 \text{ kips} > W_t = 5.1 \text{ kips}$$

Yes, the container will be carried away.

P2.22. Consider the building in Figure P2.22, which has a width into the page of 35 ft. Maximum inundation height, h_s , and flow velocity, u_s have been determined as 33 ft

and 20 ft/sec, respectively. Calculate the hydrodynamic and hydrostatic resultant load and location on the walls ABC and $IJKL$ for Load Cases 2 and 3, due to both inflow and outflow directions. If windows are inundated, calculate the expected hydrostatic loading on the adjacent outside walls due to water retained by the floor, or floors. Finally, calculate the debris impact load to be applied to the free-standing column CD . Assume $I_s = 1.0$ and $C_s = 1.25$.



P2.22

Load Case 2:

$$\frac{2}{3} h_{max} = h_{des} = 22 \text{ ft}$$

$$u_{max} = u_{des} = 20 \text{ ft/sec}$$

Hydrodynamic, Load Case 2

$$h = \text{Trib height} = 8 + 6 = 14 \text{ ft}$$

$$E = \frac{1}{2} \rho C_d C_{MB} C_{h,0} u^2$$

$$F = \frac{1}{2} \rho C_d (1.0)(1.25)(1.0)(35)(14)(20)^2$$

$$h = \frac{2}{3} h_{max}$$

Hydrostatic on interior walls

$$F = \frac{1}{2} \rho g b h^2 = \frac{1}{2} (62.4) (35) (3)^2$$

$$[r_s = 1.1 \text{ ops}]$$

Load Case 3:

$$h_{max} = h_{des} = 33 \text{ ft}$$

$$\frac{1}{32} u_{max} = u_{des} = 6.67 \text{ ft/sec}$$

Hydrodynamic, Load Case 3

$$h_s = \text{Trib height} = 1 + 8 = 9 \text{ ft}$$

$$F = \frac{1}{2} \rho C_d (1.0)(1.25)(1.0)(35)(9)(6.67)^2$$

$$[r_s = 1.1 \text{ ops}]$$




$$h = \frac{2}{3} h_{max}$$

$$h = \text{Trib height} = 8 + 8 = 16 \text{ ft}$$

$$F = \frac{1}{2} \rho C_d (1.0)(1.25)(1.0)(35)(16)(6.67)^2$$

$$[r_s = 1.1 \text{ ops}]$$

$$F = 1096.2 \text{ kips}$$




Load Case 3

Debris Impact on CD

$$E = 330 C_d I_s = 330 (0.65) (1.0)$$

$$[r_s = 214.5 \text{ ps}]$$



Hydrostatic on inside walls

2-27


Copyright© 2018 McGraw-Hill Education. All rights reserved.

No reproduction or distribution without the prior written consent of McGraw-Hill Education.




Design Loads and Structural Framing


Chapter 2




a




© Taichiro Okazaki






Copyright© McGraw-Hill Education. All rights reserved. No reproduction or distribution without the prior written consent of McGraw-Hill Education.



3




Copyright© McGraw-Hill Education. All rights reserved. No reproduction or distribution without the prior written consent of McGraw-Hill Education.

a

$\frac{1}{2}a + b + c + @$
 $\frac{1}{2}a + b + c + @$

1_B



e
 f
 g
 h
 $I^h - (I)$
 $B2$


3@
(a)

#


$w_p = 0.71 \text{ kip/ft}$


#

8.875 ps
 8.875 kips p
 $8 \quad 8 \quad 8'--]$




Copyright© McGraw-Hill Education. All rights reserved. No reproduction or distribution without the prior written consent of McGraw-Hill Education.






a




(a) Plan



$R = 32.3$ kips

(b) Elevation


a




(c) Tributary area to column C shown shaded




(d) Beam A




(e) Beam B









W = Combined weight on the first two axles, which is the same as for the corresponding Design Truck
 V = Variable spacing—14 ft to 30 ft inclusive. Spacing to be used is that which produces maximum stresses.



a









© Chia-Ming Uang

a




(a)




(b)

a





(a)



(b)

a







a



©AP Images

a





3




@Aaron Roeh Photography


a




a




a




a









Cases 1 and 2
Cases 1 and 2




a



a



(c)



$M_1 = 300.6 \text{ kip} \cdot \text{ft}$

(d)

a




© Frieder Seible




@ Chia-Ming Uang

a




(a)




(b)


a




a




(a)




(b)




a






3



a




a



© Taichiro Oazaki

a




(a) Front view


(b) Side view

(a) Front view


(b) Side view


a







Section








Section






Building Section


a



a





Mechanical Floor Plan
 Mechanical Floor Plan
 (beams not shown)
 (a)




Section
 (b)

a






(a)





Section

(b)



a





Roof slope factor C_s ,
with warm roofs and $C_s \leq 1.0$

a

